Date Printed: 4/23/2007 PROTO PVC CORP. CLEARWATER, FLORIDA 33762 727-573-4665

Product Code: MFA-300 CL

Product Name: ADHESIVE FASTENER WELD & LAP SEALER

MANUFACTURED BY:

COLORADO PAINT COMPANY II, 4747 HOLLY STREET, DENVER, CO 80216

24-hour Emergency Phone: 1-800-424-9300

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

(See top of page)

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component/Exposure Limits	CAS#	% by Wt.	
TETRAHYDROFURAN	109-99-9	45-<60	
OSHA PEL: 200 PPM, ACGIH PEL: 200 PPM			
VINYL RESIN	9003-22-9	20-<30	
(NO EXPOSURE LIMITS ESTABLISHED)			
* METHYL ETHYL KETONE	78-93-3	20-<30	
OSHA PEL: 200 PPM, ACGIH TLV: 200 PPM			
ACETONE	67-64-1	1-<5	
OSHA PEL: 750, ACGIH TLV: 750			
ISOPROPANOL	67-63-0	1-<5	
OSHA PEL: 400 PPM, ACGIH TLV: 400 PPM			
VINYL ACETATE	108-05-4	.1-<5	
10 PPM, TWA 8, OSHA & ACGIH; 20 PPM, STEL, OSHA & ACGIH			

3. HAZARDS IDENTIFICATION

EXPOSURE TO THIS MATERIAL THROUGH BREATHING SWALLOWING OR SKIN ABSORBTION CAN CAUSE INTESTINAL UPSET, IRRITATION, CENTRAL NERVOUS SYSTEM DEPRESSION

Potential Health Effects

EYE:

MAY CAUSE MILD EYE IRRITATION. SYMPTOMS INCLUDE STINGING, TEARING AND REDNESS AND POSSIBLE BLURRED VISION.

SKIN

CAN CAUSE SKIN IRRITATION. PROLONGED CONTACT MAY DRY SKIN. SYMPTOMS MAY INCLUDE REDNESS, BURNING, DRYING, CRACKING OF SKIN, BURNS AND OTHER SKIN DAMAGE.

INGESTION:

CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING AND DIARRHEA. ASPIRATION OF MATERIAL INTO THE LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL.

Page: 1

Date Printed: 4/23/2007 Page: 2

Product Code: MFA-300 CL

Product Name: ADHESIVE FASTENER WELD & LAP SEALER

COLORADO PAINT COMPANY II, 4747 HOLLY STREET, DENVER, CO 80216

24-hour Emergency Phone: 1-800-424-9300

INHALATION:

EXCESSIVE INHALATION OF VAPORS CAN CAUSE NASAL AND RESPIRATORY IRRITATION, AND CENTRAL NERVOUS SYSTEM EFFECTS INCLUDING, DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, AND HEADACHE AND POSSIBLE UNCONSCIOUSNESS.

CHRONIC (CANCER) INFORMATION:

TETRAHYDROFURAN HAS SHOWN SLIGHT INCREASE IN KIDNEY CANCER IN MALE MICE AND INCREASED LIVER CANCER IN FEMALE MICE. THE RELEVANCE TO HUMANS IS UNCERTAIN

TERATOLOGY (BIRTH DEFECT) INFORMATION:

COMPONENTS OF THIS MATERIAL HAVE BEEN SHOWN TO HARM THE FETUS. HARM OCCURS AT LEVELS THAT HARM THE PREGNANT ANIMAL, RELEVANCE OF THESE FINDINGS TO HUMANS IS UNCERTAIN

REPRODUCTION INFORMATION:

NO INFORMATION

4. FIRST AID MEASURES

EYES:

FLUSH WITH WATER, FOR 15 MINUTES REST EYES 30 MINUTES. IF REDNESS, SWELLING OR BURNING PRESIST CONSULT PHYSICIAN.

SKIN:

REMOVE CONTAMINATED CLOTHING WASH CONTACT AREA WITH SOAP AND WATER. GET MEDICAL ATTENTION IF AN ADVERSE REACTION RESULTS.

INGESTION:

DO NOT INDUCE VOMITING. RINSE MOUTH OUT WITH WATER. GET MEDICAL ATTENTION.

INHALATION:

REMOVE VICTIM TO FRESH AIR, PROVIDE OXYGEN IF BREATHING IS DIFFICULT. GIVE ARTIFICIAL RESPERATION IF NOT BREATHING. GET MEDICAL ATTENTION.

NOTE TO PHYSICIANS: PREEXISTING DISORDERS OF FOLLOWING ORGANS MAY

BE AGGRIVATED BY EXPOSURE; SKIN, LUNG, LIVER,

Date Printed: 4/23/2007 Page: 3

Product Code: MFA-300 CL

Product Name: ADHESIVE FASTENER WELD & LAP SEALER

COLORADO PAINT COMPANY II, 4747 HOLLY STREET, DENVER, CO 80216

24-hour Emergency Phone: 1-800-424-9300

KIDNEY.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES:

FLASH POINT: 6 DEGREES F Method: TCC

FLAMMABLE LIMITS:

Lower flammable limit: 1.9% Upper flammable limit: 11.8%

AUTOIGNITION TEMPERATURE: 610 DEG F

HAZARDOUS COMBUSTION PRODUCTS:

CARBON MONOXIDE, CARBON DIOXIDE, HYDROGEN CHLORIDE AND VARIOUS HYDROCARBONS.

EXTINGUISHING MEDIA:

FOAM, CO2, DRY CHEMICAL

FIREFIGHTING INSTRUCTIONS:

WEAR SELF-CONTAINED BREATHING APPARATUS WITH FULL FACE PIECE OPERATED IN THE POSITIVE PRESSURE DEMAND MODE WHEN FIGHTING FIRES.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL:

SMALL: ABSORB ON PAPER, VERMICULITE, FLOOR ABSORBENT, OR OTHER MATERIAL, TRANSFER TO CONTAINERS FOR DISPOSAL. LARGE: ELIMINATE ALL IGNITION SOURCES, WEAR PROTECTIVE CLOTHING, DIKE AREA, PUMP LIQUID TO TANK, ABSORB REMAINDER AS ABOVE.

LARGE SPILL:

ELIMINATE ALL IGNITION SOURCES. STOP SPILL AT SOURCE, PREVENT FROM ENTERING DRAINS, SEWERS, STREAMS ETC. PUMP OR VACUM TRANSFER PRODUCT TO CLEAN CONTAINERS. ABSORB BALANCE, TRANSFER ABSORBANTS, SOIL ETC. TO CONTAINERS FOR DISPOSAL. IF RUNOFF OCCURS NOTIFY AUTHORITIES.

Date Printed: 4/23/2007 Page: 4

Product Code: MFA-300 CL

Product Name: ADHESIVE FASTENER WELD & LAP SEALER

COLORADO PAINT COMPANY II, 4747 HOLLY STREET, DENVER, CO 80216

24-hour Emergency Phone: 1-800-424-9300

7. HANDLING AND STORAGE

HANDLING:

ACUTE: SEE ABOVE. CHRONIC: OVEREXPOSURE TO SOME OF THE COMPONENTS IN THIS MATERIAL HAS BEEN SUGGESTED AS A CAUSE OF CENTRAL NERVOUS SYSTEM EFFECTS IN HUMANS.

STORAGE:

NEVER USE WELDING OR CUTTING TORCH ON OR NEAR DRUMS (EVEN EMPTY DRUMS) BECAUSE PRODUCT CAN IGNITE EXPLOSIVELY. ALL FIVE GALLON PAILS AND LARGER METAL CONTAINERS INCLUDING TANK CARS AND TRUCKS SHOULD BE GROUNDED AND/OR BONDED WHEN MATERIAL IS TRANSPORTED.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS:

PROVIDE SUFFICENT MECHANICAL EXAUST TO MAINTAIN EXPOSURE BELOW TLV,S.

RESPIRATORY PROTECTION:

A NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR IS ASDVISED
IN ABSENCE OF PROPER ENVIRONMENTAL CONTROL. OSHA
REGULATIONS ALSO PERMIT NIOSH/MSHA RESPIRATORS (NEGATIVE
PRESSURE TYPE) UNDER SPECIFIED CONDITIONS. ENGINEERING
OR ADMINISTRATIVE CONTROLS SHOULD BE IMPLEMENTED TO REDUCE EXPOSURE.

SKIN PROTECTION:

WEAR RESISTANT GLOVES SUCH AS: POLYVINYL ALCOHOL.

EYE PROTECTION:

CHEMICAL SPLASH GOGGLES IN COMPLIANCE WITH OSHA REGULATIONS ARE ADVISED. OSHA REGULATIONS ALSO PERMIT OTHER GLASSES.

9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: 133 DEG F

MELTING POINT: NOT DETERMINED VAPOR PRESSURE: 143 MM @68 DEG F VAPOR DENSITY: HEAVIER THAN AIR SOLUBILITY IN WATER: INSOLUBLE

SPECIFIC GRAVITY: .95

pH: N/A

ODOR: ODOR CHARACTERISTIC OF HYDROCARBON SOLVENT

APPEARANCE:

Date Printed: 4/23/2007 Page: 5

Product Code: MFA-300 CL

Product Name: ADHESIVE FASTENER WELD & LAP SEALER

COLORADO PAINT COMPANY II, 4747 HOLLY STREET, DENVER, CO 80216

24-hour Emergency Phone: 1-800-424-9300

PRODUCTS IN THIS MSDS CLASSIFICATION MAY VARY FROM A VISCOUS TRANSPARENT LIQUID TO AN OPAQUE SEMI-PASTE.

10. STABILITY AND PHYSICAL HAZARDS

CHEMICAL STABILITY (CONDITIONS TO AVOID):

STABLE

INCOMPATIBILITY:

STRONG OXIDIZING AGENTS.

HAZARDOUS DECOMPOSITION PRODUCTS:

CARBON DIOXIDE, CARBON MONOXIDE, HYDROGEN CHLORIDE

HAZARDOUS POLYMERIZATION:

NOT EXPECTED TO OCCUR.

11. TOXICOLOGICAL INFORMATION

EYE: NO INFORMATION

SKIN: NO INFORMATION

INGESTION: NO INFORMATION

INHALATION: NO INFORMATION

SUBCHRONIC: NO INFORMATION

CHRONIC/CARCINOGENICITY: NO DATA

TERATOLOGY: NO INFORMATION

REPRODUCTION: NO INFORMATION

MUTAGENICITY: NO INFORMATION

12. ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION:

NO INFORMATION

CHEMICAL FATE INFORMATION:

NO INFORMATION

13. DISPOSAL CONSIDERATIONS

Date Printed: 4/23/2007 Page: 6

Product Code: MFA-300 CL

Product Name: ADHESIVE FASTENER WELD & LAP SEALER

COLORADO PAINT COMPANY II, 4747 HOLLY STREET, DENVER, CO 80216

24-hour Emergency Phone: 1-800-424-9300

FURTHER INFO

14. TRANSPORT INFORMATIONÿ (Not meant to be all inclusive)

ADHESIVES, 3,UN1133,II

15. REGULATORY INFORMATIONŸ (Not meant to be all inclusive - selected regulations represente

U.S. FEDERAL REGULATIONS:

THIS PRODUCT AND/OR ALL OF ITS COMPONENTS ARE EITHER INCLUDED ON OR EXEMPT FROM TSCA INVENTORY OF CHEMICAL SUBSTANCES

OSHA: NOT LISTED

CERCLA: SARA HAZARD CATEGORY:

TETRAHYDROFURAN RQ 1000LBS

SECTION 313:

 * Component(s) reportable as SARA Title III section 313 chemical(s). *

INTERNATIONAL REGULATIONS:

CANADIAN WHMIS:

NO INFORMATION

CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA):

THE INTENTIONAL INGREDIENTS OF THIS PRODUCT ARE LISTED.

EINECS: THE INTENTIONAL INGREDIENTS ARE LISTED

STATE REGULATIONS:

PENNSYLVANIA, NEW JERSEY RTK LABEL INFORMATION METHYL ETHYL KETONE AND TETRAHYDROFURAN.

VOLATILE ORGANIC COMPOUNDS:

VOC < 729 GM/L

16. OTHER INFORMATION

MSDS Status: ACTIVE

WE BELIEVE THAT THE INFORMATION CONTAINED IN THE MSDS SHEET IS ACCURATE. HOWEVER, BECAUSE THIS MATERIAL CAN BE USED UNDER CONDITIONS OVER WHICH WE HAVE NO CONTROL, WE GIVE NO WARRANTY, EXPRESSED OR IMPLIED AS TO THE

Date Printed: 4/23/2007 Page: 7

Product Code: MFA-300 CL

Product Name: ADHESIVE FASTENER WELD & LAP SEALER

COLORADO PAINT COMPANY II, 4747 HOLLY STREET, DENVER, CO 80216

24-hour Emergency Phone: 1-800-424-9300

ACCURACY OF THE INFO RMATION, AND ASSUME NO RESPONSIBILITY FOR DAMAGE TO PERSON, PROPERTY, OR BUSINESS ARISING FROM ITS USE.